

High purity aluminum reflector, housing and heat sink; high strength tempered glass cover; high power LED light source; high efficiency LED driver.



City streets, pavements, squares, schools, parks, yards, residential areas, factories and any other places where lighting is needed.




## 720LD

### Street Lights

#### Light Distribution



#### Product Dimension



#### Packing size

Quantity/ Carton(Piece)  
1

Carton size (mm)  
780 × 345 × 270



CE RoHS

Model	Power W	Light Source Power (W)	Operating Voltage (V)	Power Factor	Lumen Output lm		Weight Kg
720LD33(1)	33	30	100-240AC/24DC/12DC	≥ 0.92	2640	2970	10.24
720LD45(1)	45	40	100-240AC/24DC/12DC	≥ 0.95	3600	4050	10.24
720LD55(1)	55	50	100-240AC/24DC/12DC	≥ 0.95	4400	4950	10.24
720LD65(1)	65	60	100-240AC/24DC	≥ 0.95	5200	5850	10.24
720LD80(1)	80	70	100-240AC/24DC	≥ 0.95	6000	6800	10.24
720LD90(1)	90	80	100-240AC/24DC	≥ 0.95	6750	7650	10.24
720LD100(1)	100	90	100-240AC	≥ 0.95	7500	8500	10.24
720LD110(1)	110	100	100-240AC	≥ 0.95	8250	9350	10.24

IP Rating (IP)  
IP65

Ambient Temperature (°C)  
-40~50

Color Temperature (K)  
3000k 3045 ± 175  
4000k 3985 ± 275  
5000k 5028 ± 283  
5700k 5665 ± 355