

# TRACER Maximum Power Point Tracking

## Solar controller



Tracer series controller adopts latest MPPT technology (Maximum Power Point Tracking) and advanced tracking algorithm to make the solar module operate at ideal voltage which the solar modules can produce the maximum available power.

Compared to conventional PWM controller, MPPT technology increases the charge efficiency up to 30% and potentially decrease the power of solar array needed.

The ability to step-down the higher voltage solar module to recharge a lower voltage battery bank greatly increases system design flexibility. The cable size can be reduced because of the small current from the solar array.


### Optional Accessories :

remote meter MT-5



### Features:

- ◆ MPPT technology
- ◆ Peak conversion efficiency of 97%
- ◆ High Tracking efficiency of 99%
- ◆ Several seconds tracking speed
- ◆ 4-Stage charge with PWM output
- ◆ Nature convection cooling
- ◆ Full power output up to 45 °C
- ◆ Temperature compensation
- ◆ Sealed, Gel and Flooded battery option
- ◆ Diversified load control
- ◆ RJ45 interface & optional meter
- ◆ 2 years warranty
- ◆ CE certificate



### Electronic protection:

- ◆ PV Array Short Circuit
- ◆ PV Overvoltage
- ◆ PV Overcurrent
- ◆ Load Overload
- ◆ Load short circuit
- ◆ PV Reverse Polarity
- ◆ Battery Reverse Polarity
- ◆ High Voltage Transients



# TRACER MPPT Solar Controller

Electrical parameters	Tracer-1210RN Tracer-1215RN	Tracer-2210RN Tracer-2215RN	Tracer-3215RN	Tracer-4210RN
Nominal System Voltage	12V/24V auto work			
Rated Battery Current	10A	20A	30A	45A
Rated Load Current	10A	20A	20A	20A
Maximum Battery Voltage	32V			
Max. Solar Input Voltage	60VDC (Tracer-1206RN)	--	--	--
	100VDC (Tracer-1210RN)	100VDC (Tracer-1210RN)	--	--
	150VDC (Tracer-1215RN)	150VDC (Tracer-2215RN)	150VDC (Tracer-3215RN)	100VDC (Tracer-4210RN)
Max. PV input power	12V 130W	12V 260W	12V 390W	12V 585W
	24V 260W	24V 520W	24V 780W	24V 1170W
Self-consumption	≤10mA(24V)			
Communication	TTL232 / 8pin RJ45			
Temp. compensation	-30mV/°C/12V (25°C)			

Mechanical Parameters	Tracer-1210RN Tracer-1215RN	Tracer-2210RN Tracer-2215RN	Tracer-3215RN	Tracer-4210RN
Overall dimension	156x97x68mm	169x118x83mm	242x169x91mm	242x169x91mm
Mounting holes	147x60mm	160x80mm	180x160mm	180x160mm
Terminal	4mm <sup>2</sup>	10mm <sup>2</sup>	25mm <sup>2</sup>	25mm <sup>2</sup>
Net weight	0.55kg	0.95kg	2kg	2.05kg

Environmental parameters	
Working temperature	-35°C to +55°C
Storage temperature	-35°C to +80°C
Humidity	10%-90% NC
Enclosure	IP30